

MAGNETIC STIRRER

MSB SERIES

MSB series magnetic stirrer, mainly used for stirring or simultaneous heating and stirring low viscous liquid or solid liquid mixtures. The sample temperature can be heated and controlled according to the specific experimental requirements to maintain experimental required temperature condition to ensure liquid mixing.

PRODUCT FEATURES

- Backlit LCD display set and current values, clear and intuitive;
- DC brushless motor, stepless speed adjustable encoder, low noise, maintenance-free, smooth operation;
- A variety of operating modes ensure that the stirring function does not change due to external factors;
- With positive and inversion function and program editing function, positive & reverse switching, temp switch can be achieved, fully stirring;
- High temp resistant strong magnetic steel to ensure sufficient suction force and torque, stirring effect is significant.



Product Model	LCH-MSB-H	LCH-MSB-HD
Image		
Voltage (V)	AC110/220	
Frequency (Hz)	50-60	
Power (W)	450	550
Display Mode	/	LCD
Max Stirring H ₂ O Volume (L)	5	
Temperature Range (°C)	RT-300	RT-300
Speed Range (rpm)	200-1600	100-1600
Timing Range	/	1-99h59min
Working Size (mm)	150*150	
Material of Working Plate	Cast aluminum + Ceramic spraying	
Motor Type	DC Brushless Motor	